# ((gtx

# FLARE-1000

LED Vertical Fog Machine

Item ref: 160.486UK User Manual

#### 0 • FLARE-1000 (+) **慢qtx** A 0000000 . 00000000 • • • 0 : • 0000000 • G • A DO NOT COVER VENTS NOT OPEN • 600 . . MIN 000000 (EXLIG® FLUID LEVELS



Caution: Please read this manual carefully before operating Damage caused by misuse is not covered by the warranty

#### Introduction

Thank you for purchasing the FLARE-1000 LED vertical fog machine. This product has been designed to provide dramatic, illuminated fog effects for stage productions and themed events. Please read and keep this manual in order to achieve the best results from this equipment and avoid damage through misuse.

#### Unpacking

The product should arrive with you in good condition with the following components.

- FLARE-1000 LED vertical fog machine
- Wireless remote receiver
- Key fob remote control
- Mains lead(s)

If you find any accessory is missing or the machine has arrived with any problems, please contact your local dealer at once. Please keep the original package and invoice for any possible replacement or returned demand.

#### Warning

To prevent risk of fire or electric shock, do not expose electrical parts to rain or moisture. If liquids are spilled on areas other than inside the fluid tank, disconnect the mains, allow the FLARE-1000 to dry out and have it checked by qualified personnel before further use. Avoid any impact, dropping or extreme pressure to the housing.

No user serviceable parts inside - do not open the case.

Allow the FLARE-1000 to acclimatize to room temperature before operating.

#### Placement

The FLARE-1000 has a built-in fluid container and should be operated in an upright position. Ensure that the FLARE-1000 is positioned on a stable, non-slip surface.

#### Safety

- Check for correct mains voltage and condition of IEC lead before connecting to mains
- This unit must be earthed
- This unit uses a heating element be aware that parts of the housing may be hot in use!

#### Cleaning

- Use a soft dry or slightly damp to clean the casing
- Do not use strong solvents for cleaning the housing
- Clean the fog mechanism periodically by operating with distilled water instead of fog fluid
- It is also recommended to use fog machine cleaning fluid (160.670UK) periodically

#### **Recommended fluid**

For the FLARE-1000 fog machine, we strongly recommend the following fluids, which have been formulated to perform best with any heater-based fog machines.

QTX ref. code	Description	Size
160.583UK	High Quality Fog Fluid (pink)	5 Litre
160.588UK	High Grade Fog Fluid (orange)	5 Litre
160.589UK	Premium Fog Fluid (clear)	5 Litre

The FLARE-1000 has a labelled window in the side panel to show the fluid level in the bottle. Check this level periodically to ensure that the FLARE-1000 does not run empty.


#### Use power supply with Earth connection and adequate current capacity for the unit

Use the plug to connect to the main power supply as follows:

Wire colour	Connection	International symbol
Brown	Live	L
Blue	Neutral	Ν
Yellow / Green	Earth	-

#### **Connection panel**

- 1 RF remote receiver connection
- 2 Power on/off switch
- 3 LCD display
- 4 4 button control panel
- 5 DMX input (3-pin XLR)
- 6 DMX output (3-pin XLR)
- 7 IEC mains inlet & fuse holder



### Setting up

- 1. Unscrew the top cap of the fluid tank and remove to fill with fog fluid.
- 2. Replace the bottle and screw the cap securely, making sure that the pipe is fed down to the bottom of the bottle to ensure a consistent flow of fluid.
- 3. Connect the RF remote receiver to the 5-pin DIN socket (1) on the side panel.
- 4. If DMX is to be used for control, connect the DMX signal from the controller to the DMX IN XLR connector (5). Any further DMX controlled units may be connected via the DMX OUT XLR connector (6).
- 5. Connect the IEC mains plug (7) and switch the power on (2).
- 6. After heat-up of 3-5 minutes, the green LED on the remote receiver will light.
- 7. The FLARE-1000 is now ready to use.

## Operation

DMX start address and LED light settings for the FLARE-1000 are made using the control panel and display (3, 4) as described below.

Press MODE	Press ▲▼ and ENTER	Function
Я	800 I - 85 I2	DMX start address 001 to 512
Ρ	P000	No function
r	r000 - r255	Red LED 0-100% brightness
9	9000 - 9255	Green LED 0-100% brightness
Ь	6000 - 6255	Blue LED 0-100% brightness


Direct control is available using the RF wireless remote control. Connect the wireless remote receiver to the 5-pin DIN socket on the connection panel, extend the antenna on the key fob remote and operate from the 4 buttons as described below.

R = Fog with red LEDs on

G = Fog with green LEDs on

- B = Fog with blue LEDs on
- FOG = Fog with no LEDs on

Press to activate, release to stop fog output.



#### **DMX** operation

If a DMX signal is connected, the unit will operate from DMX as follows.

DMX Channel	Value	Function
CH1 (start address)	000-255	Fog volume setting (1%-100%)
CH2	000-255	RED 0%-100% dimming
CH3	000-255	Green 0%-100% dimming
CH4	000-255	Blue 0%-100% dimming
CH5	000-255	Strobe speed 0%-100%
	000-030	LED auto program off
CH6	031-104	LED light auto colour scroll
СПО	105-179	LED light auto colour switch
	180-255	LED light auto colour pulse
CH7	000-255	LED Light Auto Program Speed Adjustment

#### Specifications

Power supply	220-240Vac, 50Hz (IEC)
Power consumption	1000W
Fuse	F5AL
Warm up time	3-5 minutes
Fog output	6000 cu ft (170m³) /min
Fluid capacity	1 Litre
LEDs	6 x 1W tri-colour RGB
Controller	RF remote or DMX512 control (7 channels)
Remote control	RF 433MHz (23AE 12V battery)
Dimensions	315 x 215 x 170mm
Weight	3.69kg

#### Troubleshooting

Warning: Hot components! ... Switch off and allow to cool before touching the unit.

	Check mains voltage is correct and socket is switched on
No light on mains	Check IEC lead is OK and connected properly
switch or remote	Check mains fuse in IEC connector and fuse in plug top
	If fuse blowing repeatedly, refer to qualified service personnel
	Check fluid level in tank
Green light is on but no	If fluid is OK and pump working, the lines may be blocked
fog output on manual	If blocked, clean with fog machine cleaner & distilled water
or continuous mode	Check that if DMX mode is selected, the DMX channel is correct
	In DMX mode, check that fog output is not set to zero



This product is classed as Electrical or Electronic equipment and should not be disposed with other household or commercial waste at the end of its useful life. The goods must be disposed of according to your local council guidelines.

#### Errors and omissions excepted.

Copyright© 2021 AVSL Group Ltd, Unit 2 Bridgewater Park, Taylor Road, Trafford Park, Manchester. M41 7JQ.

xubツ				ETTECTS P	Effects Fluid Chart			
<b>Bubble Fluid</b>								
Stock Code	Volume	Description			Res	Results		For use with
160.574UK	1 Litre	Buckho fluid			licht long l	cting hubbles		
160.575UK	5 Littre	םמחחוב ווחומ			LIBIIL, IUIIB-IA	כבוטטטט פוווזכפו-פווטו לוופט		160.462UK, 160.560UK 160.562UK, 160.563UK
160.576UK	1 Litre	UV bubble fluid			ight bubbles whi	ieht bubbles which glow in UV light	+	160.564UK
160.577UK	5 Littre				0	0		
Snow Fluid								
Stock Code	Volume	Description			Res	Results		For use with
160.578UK	-							
160.579UK	5 Littre	- Snow fluid		High quality sno	w fluid.Lasts 30%	High quality snow fluid.Lasts 30% longer than other standard fluids	er standard fluids	160.565UK, 160.569UK
Fog Fluid								
	-				Res	Results		
STOCK LODE	volume	nescription	COLOUIL	Dispersion	Density	Stability	Fog colour	For use with
160.643UK	1 Litre	Standard fog fluid	Yellow	Quick	Light	Low	White	
160.582UK	5 Littre							100.452UK, 100.453UK, 100.401UK
160.587UK	1 Litre	High grade fog fluid	Orange	Slow	Medium	Good	White	or any machine up to 900W
VD00C-DDT	2000							
160.583UK	5 Litre	<ul> <li>High quality fog fluid</li> </ul>	Pink	Slow	High	Good	Thick white	160.455UK, 160.456UK, 160.457UK
160.589UK	5 Litre	Premium fog fluid	Clear	Slow	Verv high	Excellent	Opaque White	or any machine 1000-1500W
160.592UK	1 Litre	-	1	-	•	:	-	
160.593UK	5 Litre	<ul> <li>Low level tog fluid</li> </ul>	Clear	Slow	Highest	Excellent	Opaque White	160.447UK
160.670UK	20ml	Fog machine cleaner	Clear		Extends life of y	Extends life of your fog machine		All fog machines
<u>Haze</u>								
	-				Res	Results		
STOCK LODE	Volume	Description	Colour	Dispersion	Density	Stability	Haze colour	For use with
160.591UK	5 Litre	5 Litre High quality haze fluid	Close	Slow	High	Good	Thick white	VI1326 021 VI1C26 021 VI1026 021 VI1026 021
160.591UK	5 Littre	5 Littre Eco haze fluid	CIEGI	Medium	Medium	Good	White	TUU-4000V, TUU-4020V TUU-4020V, TUU-4000V
Fog								
Stock Code	Volume	Description			Res	Results		For use with
160.650UK	20ml	Coconut fog fragrance						
160.651UK	20ml	Mint fog fragrance						
160.652UK	20ml	Vanilla fog fragrance			Adde framoe	to for or have		20ml – 5 Litro for or boro fluid
160.653UK	20ml	Tropical fog fragrance			Auna li agrance	AUDI 10 801 01 AUDI 1976		בטוווו = 2 נותב וספ טו וומגב וותומ
160.654UK	20ml	Strawberry fog fragrance						
1 CO CELIN								